

BRO New Generation U series Agriculture Drone





Foldable Arm



Integrated FC



FPV Gimbal



Waterproof and Dustproof



Weight Sensor



Large-flow Impeller Pump



New generation U series agriculture drone will bring you wonderful experience.

New designed truss- style structure with foldable arms to reduce the body size, compatible with spraying and spreading functions.

Equipped with Bro Mini Ultra-wide Angle FPV gimbal, which makes operator has a wide vision on the field and drone mapping more flexible and convenient.

U40,U60 can meet different scenarios operation needs.







Folded arms for convenient carry and transportation.



High strength structure greatly reduce the maintenance cost.



Highly integrated flight controller achieve perfectly software and hardware integration




Weight sensor real-time remaining pesticide monitoring



Water-cooling centrifugal nozzles stronger penetration and smaller atomized articles



Pluggable and integrated spraying tank can quickly be swapped with spreading tank





MECHANICAL LOCK

Special innovative mechanical lock, avoid the accident caused by unlocking

LOCK SENSOR

Dual protection, no locking, no flying





1080P FULL HD STARLIGHT FPV


Bro mini FPV gimbal's ultra-sensitive starlight CMOS can keep image bright even in low light environment.





U40 and U60 can both spray pesticide and spread solid fertilizer or seeds.

The all-new integrated spraying system can quickly be swapped with spreading system. The spreading tank capacity of U40 and U60 are 50L and 80L.



The new version spreader adopts upper and lower segmented drive shaft design. Screws are screwed externally, so won't stick fertilizers and can be easily disassembled and assembled from outside. The motor wiring is external to prevent fertilizers and liquids from entering the electric control hatch



AB point memory operation



Data Cloud Storage



Field Planning



Obstacle avoidance radar



Real-time Battery Monitoring



Night Navigation **Function**



Aircraft Breakpoint Memory



Empty tank warning



Manual Operation Mode



Position Retention Mode



Terrain Following Radar



Carbon Fiber Arm



Excellent Battery Life



(HD Fpv Camera



High-precision GPS system



IP67 Rating for Core Modules





		U40	U60
Airframe	Airframe Dimensions (incl.propellers)(mm)	2560mm*2460mm*790mm	3060mm*3050mm*840mm
	Transport Dimensions (mm)	940mm*715mm*810mm	1110mm*800mm*865mm
	Max Takeoff Weight (kg)	90	110
	Water-resistant	IP67	IP67
Flight Control System	Flight Controller	High Integrated Agricultue Intelligent System	High Integrated Agricultue Intelligent System
	Night Operation		
	Obstacle Avoidance	✓	✓
	MMW Radar Terrain Tracing		✓
	Terrain Tracing Accuracy (m)	<0.5	<0.5
	Navigation Method	Dual RTK module system+GPS	Dual RTK module system+GPS
Spraying System	Maximum Capacity (kg)	35	55
	Spraying Tank(L)	35	55
	Spreading Tank(L)	50	80
	Spraying Width (m)	6-10	8-12
	Efficiency (ha/mission)	2	3.3
	Nozzle Type	Centrifugal Nozzles	Centrifugal Nozzles
	Droplet Size(μm)	50-500 μ m	50-500 μ m
	Breakpoint Resume		
	Instant Flow-start/stop	✓	√
	Operating Efficiency [ha/hr]	12	20
	Flowmeter/level Gauge	✓	✓
Power System	Battery Capacity (mAh)	14S 30000*1	18S 30000*1
7	Battery Warranty (Cycle)	1 Year or 1000 cycles	1 Year or 1000 cyeles
	Charging Time(min.)	10	10
Remote Control System	Integrated Intelligent Remote Controller	✓	√
7	Charger		
	FPV	1080P Single Axis Gimble	1080P Single Axis Gimble






High Brightness Widescreen Remote Controller

BROUAV S2 RC has a 7-inch high brightness screen and an 8-core processor for smooth operations.


Intelligent route planning minimizes distances flown with a full tank, greatly increasing operation efficiency.

Manual mode allows you to control operations at will.






7 inch screen 1920*1080,1500 nits LCD



OFDM multi-carrier m odulation





>> SMART LITHIUM BATTERY



BRO smart lithium battery uses high energy cells and an advanced power management system to provide long-lasting power to BRO U series drone. The optimized battery cells and heat dissipation design effectively keep the temperature of the battery in check.

BRO intelligent charger supports single phase and three phase AC power input. Three phase AC input is the fast charging model, which can charge the relative battery fully in 10~15minutes. Additionally, the charger includes overcurrent protection, overcharging protection, under-voltage protection, overheating protection, and status display.




✓ Large Capacity

✓ Fast Charging

Overcharging Protection

✓ Overcurrent Protection ✓ Over Voltage Protection ✓ Short Circuit Protection



Contact Us

- **** +62 851-1723-7833
- agrominaofficial@gmail.com
- agrominabiotech.com
- Podomoro Golf View Ruko Granada B3-10 Jl. Mochamad Thohir, Desa Bojong Nangka, Kec. Gunung Putri, Kab. Bogor 16963